

Wenzhou Huida Plastic Co.,Ltd.

No.168 Huanshan Road,Dongmeng Industrial Zone,Wuniu Town,Wenzhou,Zhejiang,China www.wzh

TELL:86-577-67307917 FAX:86-577-67307911 CELL:86-13736760755 sarahwu@hds-cabletie.com

Datasheet for Heat Shrinkable Tubings

Type	Dimension before shrinking(mm)		Dimension after shrinking(mm)		Packing m/disc	Application (mm)
	Internal diameter	Wall thickness	Internal diameter	Wall thickness		
Φ0.8	0.9±0.2	0.20±0.05	0.40±0.1	0.32±0.05	200	0.6-0.8
Φ1.0	1.2±0.3	0.20±0.05	0.48±0.1	0.32±0.05	200	0.75-0.9
Φ1.5	1.7±0.3	0.20±0.05	0.73±0.1	0.32±0.05	200	0.95-1.4
Φ2.0	2.2±0.3	0.25±0.05	0.98±0.1	0.32±0.05	200	1.1-1.8
Φ2.5	2.6±0.3	0.25±0.05	1.23±0.2	0.35±0.05	200	1.35-2.3
Φ3.0	3.2±0.4	0.25±0.05	1.45±0.2	0.35±0.05	200	1.6-2.7
Φ3.5	3.6±0.4	0.25±0.05	1.72±0.2	0.35±0.05	200	1.85-3.2
Φ4.0	4.2±0.4	0.25±0.05	1.96±0.2	0.35±0.05	200	2.1-3.6
Φ4.5	4.6±0.4	0.25±0.05	2.20±0.2	0.35±0.05	200	2.35-4.0
Φ5.0	5.2±0.4	0.25±0.05	2.48±0.2	0.35±0.05	200	2.6-4.5
Φ6.0	6.2±0.4	0.28±0.15	2.96±0.3	0.45±0.15	200	3.1-5.4
Φ7.0	7.2±0.4	0.28±0.15	3.48±0.3	0.45±0.15	100	3.7-3
Φ8.0	8.2±0.5	0.28±0.15	3.95±0.3	0.45±0.15	100	4.2-7.2
Φ9.0	9.2±0.5	0.30±0.15	4.40±0.3	0.50±0.15	100	4.7-8.0
Φ10	10.2±0.5	0.30±0.15	4.90±0.3	0.50±0.15	100	5.2-9.0
Φ11	11.2±0.5	0.30±0.15	5.40±0.3	0.50±0.15	100	5.7-10
Φ12	12.2±0.5	0.30±0.15	5.90±0.5	0.50±0.15	100	6.2-11
Φ13	13.2±0.5	0.33±0.15	6.40±0.5	0.50±0.15	100	6.7-12
Φ14	14.2±0.5	0.35±0.15	6.90±0.5	0.50±0.15	100	7.3-13
Φ15	15.2±0.6	0.38±0.15	7.40±0.5	0.60±0.15	100	7.8-14
Φ16	16.2±0.6	0.38±0.15	7.90±0.5	0.60±0.15	100	8.3-15
Φ17	17.2±0.6	0.38±0.15	8.40±0.5	0.60±0.15	100	8.8-16
Φ18	18.2±0.6	0.40±0.15	8.90±0.5	0.60±0.15	100	9.3-17
Φ20	20.2±0.8	0.40±0.20	9.90±0.5	0.70±0.20	100	11.4-19
Φ22	22.2±0.8	0.42±0.20	10.80±1.0	0.70±0.20	100	12.4-21
Φ25	25.3±0.8	0.45±0.20	12.30±1.0	0.70±0.20	50	12.8-24
Φ28	28.3±0.8	0.45±0.20	13.50±1.0	0.70±0.20	50	14.4-29
Φ30	30.2±0.8	0.45±0.20	14.70±1.0	0.70±0.20	50	16-29
Φ35	35.2±0.8	0.50±0.20	17.30±1.0	0.80±0.20	50	18-34
Φ40	40.0±1.0	0.50±0.20	19.80±1.0	0.80±0.20	50	21-39
Φ50	50.0±1.0	0.50±0.20	24.80±1.0	0.80±0.20	50	26-49
Φ60	60.0±1.0	0.60±0.20	29.80±1.0	0.80±0.20	25	35-55
Φ70	70.0±1.0	0.65±0.20	34.00±2.0	1.00±0.20	25	40-65
Φ80	80.0±1.0	0.65±0.20	39.00±2.0	1.00±0.20	25	45-75
Φ90	90.0±1.0	0.65±0.20	44.00±2.0	1.00±0.20	25	50-88
Φ100	100.0±2.0	0.65±0.20	49.00±2.0	1.00±0.20	25	55-95
Φ120	120.0±2.0	0.70±0.20	59.00±2.0	1.20±0.20	25	65-115
Φ150	150.0±2.0	0.70±0.20	74.00±2.0	1.20±0.20	25	80-145
Φ180	180.0±2.0	0.70±0.20	88.00±2.0	1.20±0.20	25	95-175